

# TREE GRATES



Wausau Tile's decorative tree grates are the perfect blend of form and function. Available with recesses and drainage slots.

Standard color options include Weatherstone, Light Grind, Ground & Polished and Acid Wash and can be viewed at [WausauTile.com](http://WausauTile.com).

PROPERTY	ADVANCED TESTING VALUE	TEST METHOD
Compression Strength	Wausau Tile standard is 5000 PSI at 28 days.	ASTM C39
Water Absorption	Wausau Tile standard is less than 6%.	ASTM C642
Flexural Strength	Non-Standard	ASTM C78 (3rd party test: American Engineering)
C373 Water Absorption	Not-Applicable	
C482 Bond Strength	Not-Applicable	
C485 Warpage Edge	Tolerance of +/- 1/8"	100% Visual inspection of product, Straight edge confirmation as needed.
C485 Warpage Diagonal	Tolerance of +/- 1/8"	100% Visual inspection of product, Straight edge confirmation as needed.
C499 Nominal Size	Tolerance of +/- 1/8"	100% Inspection, Measurements verified against fabrication drawings.
C499 Thickness	Tolerance of +/- 1/8"	100% Inspection, Measurements verified against fabrication drawings.
Dynamic DCOF	Non-Standard, As specified for walking surfaces only.	ANSI 326.32017 (3RD PARTY: TCNA)
ANSI A173.1 Section 9.6.1	Not-Applicable (Tile only)	
Avg. Polished Finish	100% Visual Inspection	Visually compare product to control sample
Avg. Honed Finish	100% Visual Inspection	Visually compare product to control sample
Freeze/Thaw	Non-Standard	ASTM C666 (3rd Party, American Engineering)
Center Load	Not-Applicable (Pavers only)	

**CALL FOR FURTHER DETAILS & PRICING.**

P: 800.388.8728 | E: [wtile@wausautile.com](mailto:wtile@wausautile.com) | [WAUSAUTILE.COM](http://WAUSAUTILE.COM)