

Concrete Specification

1.1 SUMMARY

- A. Section includes: Furnish Precast Concrete indicated on drawing or specified herein.

1.2 REFERENCES

- A. American Society for Testing & Material
 - 1. ASTM C33
 - 2. ASTM C150
 - 3. ASTM C31

1.5 SUBMITTALS

- A. Submit Product data, shop drawings and samples.
 - 1. Product Data: Manufacturer's specifications and technical data edited specifically for proposed system, including the following specific Information:
 - a: Detailed specification of construction fabrication.
 - b: Manufacture's installation instructions
 - c: Maintenance literature
 - d: Product warranty
 - 2. Shop Drawings: Indicate pertinent dimensions, general construction, component connections anchoring methods, hardware and installation procedures.
 - 3. Samples as requested by Architect.

1.6 QUALITY ASSURANCE

- A. Qualifications of Manufacture: Manufacturer to be prequalified by specifier prior to bidding. Failure to comply will result in disqualification of bid. Manufacturer to have at least five years' experience in the manufacture of precast concrete field proven for at least five years.

1.10 WARRANTY

Manufacturer shall submit a written warranty for precast products for the period of two years upon acceptance.

2.1 MANUFACTURERS

- A. Acceptable manufacturer for Precast Concrete to be know as Wausau Tile, Inc.
P.O. Box 1520
Wausau, WI 54402-1520
(800) 388-8728 (715) 359-3121 FAX (715) 355-4627
- B. Clarification Note: Drawings and installation specification are based on manufactures proprietary literature from Wausau Tile, Inc. other manufacturers shall comply with minimum levels of material and detailing indicated on drawings of specified herein.
- C. All Precast products for this project shall be of one manufacturer.

2.2 MATERIALS

- A. Portland cement: ASTM C150 specifications for Portland cement.
- B. Aggregates: All aggregates to meet ASTM C33 specifications, to be cleaned of foreign matter and properly graded to size.
- C. Coloring: Pigments used shall be inorganic, resistant to alkalinity and used as per manufacturers recommendations.

