WAUSAU TILE

LED Modules

SPECIFICATION SUMMARY

Model: RM - O1 -	13	23
Wattage @120VAC:	≤13	≤23
Lumens @ 4000K CCT:	1000	1900
Dimensions - Max Diameter / Height:	3.50in. / 1.08in.	6.18in. / 1.32in
Power:	120VAC 50/60Hz	
Available CCT:	3000K / 4000K	
CRI:	≥80	
Compliance:	UL 1598 / FCC Compliant Class B	
Power Factor:	≥.98	
Dimming:	AC Triac Standard	
L70 Lifespan (TM21 Calculated):	≥50,000 hrs.	
Optional Surge Protection:	On Board - Line Voltage	
Lens:	Optical Grade - Polycarbonate	
Max. Ambient Operating Range:	-25°C - +80°C	
Limited Warranty:	10 Yrs.	

Notes: All values nominal.

PART NUMBER SPECIFICATION

RM-O1		-	-	-
Series:	Wattage:	CCT:	Voltage:	Surge Protection
	13 (13 Watt)	30 (3000K) 40 (4000K)	120 - (120VAC)	M (Line Voltage Surge Protec - tion Installed)
	23 (23 Watt)			

PROJECT SPECIFICATION

Project:	Part Numbers:	Quantity:
Approved:		
Date:		