

# Product Information

## USB charging devices

### Product description


2-pole, 3-wire grounding  
 15A, 125V/AC, 5V DC 700MA; 15A, 125V/AC, 5V DC 2.4A;  
 15A, 125V/AC, 5V DC 3.1A  
 20A, 125V/AC, 5V DC 3.1A

### Design features

- Standard AC receptacle with two USB charging ports for conveniently charging most electronic components
- Dual USB charging ports charge most compatible electronic devices that charge via a 5V power adapter
- Three (3) pre-stripped 6" wire leads for line, neutral and ground for quick and easy installation (excluding TR7740 and TR7741)
- Tamper resistant receptacles provide compliance with 2014 NEC® Article 406.12 which states that all 15A and 20A, 125V/AC receptacles installed in dwelling units must be tamper resistant
- Automatic grounding system eliminates need for bonding jumper in grounded metal enclosure and provides redundant measure of ground continuity where jumper is used
- Thermoplastic top and back-body are virtually unbreakable to deliver years of durable performance
- Backwire clamps on side terminals provide for easy installation of #12 and #14 AWG wire (TR7740 and TR7741 only)
- Triple wipe blade contacts and double wipe ground contacts to ensure long-term plug retention
- Replaces a standard duplex receptacle and uses a decorator style wallplate



### Combination USB charger with TR receptacle



Rating A	V/AC	USB Rating A	V/DC	Description	Color suffix	Catalog no.
15	125	2.4	5	Combination USB charger with TR single receptacle	A, B, BK, GY, LA, V, W	□ TR7741__
15	125	3.1	5	USB charger with TR duplex receptacle, wire leads	A, B, BK, GY, LA, RB, SG, V, W	□ TR7755__
20	125	3.1	5	USB charger with TR duplex receptacle, wire leads	A, B, BK, GY, LA, RB, SG, V, W	□ TR7756__

cULus Listed UL 498 and UL1310; NOM certified



TR7741



TR7755



TR7756



7750

## USB charging station

### Product description

5V/DC, 5.0A Total

### Design features

- USB charging ports rated at 5.0 Amps total (2.5A top two ports, 2.5A bottom two ports)
- Three (3) pre-stripped 6" wire leads for line, neutral and ground for quick and easy installation
- Automatic grounding system eliminates need for bonding jumper in grounded metal enclosure and provides redundant measure of ground continuity where jumper is used
- Thermoplastic top and back-body are virtually unbreakable to deliver years of durable performance
- Steel mounting strap is zinc plated for added corrosion resistance
- Convenient patented built-in wire strippers speeds installation
- Replaces a standard duplex receptacle

### USB charging station



USB Rating A	V/DC	Description	Color suffix	Catalog no.
5.0	5	USB multiport charging station	A, BK, GY, LA, V, W	□ 7750__

UL Listed to UL1310

Colors selections are for charging stations only

### Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RB (Oil Rubbed Bronze), SG (Silver Granite), V (Ivory), W (White).



Compliances, specifications and availability are subject to change without notice.

Tamper resistant



P: 800.388.8728 | E: [wtile@wausautile.com](mailto:wtile@wausautile.com) | [WAUSAUTILE.COM](http://WAUSAUTILE.COM)  
 P.O. Box 1520, Wausau, WI 54402-1520



Vertical Cover



Horizontal Cover

### Features

- Complies with 2008 NEC Article 406.8(B)(1)
- 3 patented inserts for GFCI, duplex, toggle or round receptacles
- Two-gang models include 6 snap-together, rotating, inserts that create 70 combinations
- Heavy-duty polycarbonate construction
- Clear cover on most models
- Pre-adhered gasket
- Meets requirements for cold impact testing: -60°F (-51°C)

**Covers are Clear with  
Black mounting plates**

### Ratings

Cover:	Clear (gray on selected models) UV stabilized polycarbonate with two cord outlets ½" (12.7 mm) wide by ⅜" (14.2 mm) high. Models WP1050C one cord outlet ¾" (19.1 mm) wide by 1 ⅜" (33.3 mm) high
Mounting Base and Inserts:	Black UV stabilized polycarbonate
Gasket:	Neoprene - ⅛" (4.8 mm) thick with slits for mounting screws
Max Cord Size:	2 to 14 gauge or 1 to 12 gauge; Only WP1050: 2 to 14 gauge or 1 to 10 gauge
Warranty:	Limited 1 year

