



**WAUSAU TILE**

# Safety Edge Pool Coping

## ACID WASHED FINISH COLOR OPTIONS



HRT15



HRT30



HRT60



*Due to the natural variances in aggregate materials, the color characteristics of manufactured product may differ slightly from the color swatches pictured. Your monitor or printer may not be an accurate representation of the actual production color or finish.*

PROPERTY	ADVANCED TESTING VALUE	TEST METHOD
Compressive Strength	5,000 psi at 28 days	ASTM C39
Water Absorption	Less than 6% standard	ASTM C642
Non-Standard	3 <sup>rd</sup> Party Testing as required	ASTM C78
Freeze/Thaw	3 <sup>rd</sup> Party testing as required	ASTM C666
Weight	460 lbs.	N/A

## STANDARD SIZES & OTHER INFORMATION

- Dimensionally available in one foot increments up to 72" long.
- Optional widths available: 12" or 14" (3 1/4" thickness is standard)
- Safety front edge
- Initial, factory applied sealer / protectant
- Edges have a standard 1/8" radius applied to eliminate sharp edges
- Fiber reinforced
- Standard colors listed above
- Custom colors and sizes available upon request (Lead times will be extended)
- Xypex admix for waterproofing is included

**CALL FOR FURTHER DETAILS & PRICING.**

P: 800.388.8728 | E: [wtile@wausautile.com](mailto:wtile@wausautile.com) | [WAUSAUTILE.COM](http://WAUSAUTILE.COM)