




QUICK SHIP CEMENTITIOUS TERRAZZO TILE




TZ10 QS
FULL MOON




TZ23 QS
FLAX



TZ30 QS
CRUSHED ICE




SST10 QS
PISA




SST11 QS
DALMATA


QUICK SHIP EPOXY TERRAZZO TILE




TZE01 QS
SNOWBOUND




TZE02 QS
MESQUITE




TZE03 QS
ONYX



TZE04 QS
WHITE DIAMOND



TZE05 QS
NICKEL



TZE06 QS
ICE MIST



EPOXY

24" sq.
9/16"



CEMENTITIOUS

24" sq.
5/8"

QUICK SHIP TERRAZZO TILE

Quick Ship Terrazzo Tile is shipped within 4 business days of purchase, subject to availability.

Sizes include: Epoxy - 24" sq. 9/16" | Cementitious - 24" sq. 5/8" thickness

Check WausauTile.com or call your sales rep for more details.

Due to the natural variances in aggregate materials, the color characteristics of manufactured tiles may differ slightly from the color swatches pictured. Your monitor or printer may not be an accurate representation of the actual production color or finish.

PROPERTY	ADVANCED TESTING VALUE	TEST METHOD
Compression Strength	> 8,000 PSI avg. Epoxy > 13,000 PSI avg.	ASTM C140
Absorption	< 5% avg.	ASTM C140
Flexural Strength	> 1,000 PSI avg.	ASTM C293
C373 Water Absorption	Passes (Semi-Vitreous)	-
C482 Bond Strength	> 300 PSI	-
C485 Warpage Edge	+/- .001% or .002 in.	-
C485 Warpage Diagonal	+/- .003% or .010 in.	-
C499 Nominal Size	Range of .029 in.	-
C499 Thickness	Range of .029 in.	-
Dynamic DCOF	Passes at Factory	-
ANSI A173.1 Section 9.6.1	Wet Dynamic Coefficient of Friction (DCOF)	-
Avg. Polished Finish	0.46	-
Avg. Honed Finish	0.54	-

Testing based on 12" x 12" x 1/2" tile

CALL FOR FURTHER DETAILS & PRICING.

P: 800.388.8728 | E: wtile@wausautile.com | WAUSAUTILE.COM