WAUSAU TILE

TRADITIONAL SERIES TERRAZZO TILE

TZ22
PARCHMENT

TZ23
FLAX



TZ26
SAGE



TZ30
CRUSHED ICE



TZ31
COTTAGE GRAY



TZ32
OYSTER SHELL



TZ34
NIGHT OWL



TZ35
TURTLE DOVE

TZ36 PINK
CHAMPAGNE



TZ40
FRESH LIME



TZ89
SLATE



TZ90
MIDNIGHT

PROPERTY	ADVANCED TESTING VALUE	TEST METHOD
Compression Strength	> 8,000 PSI avg.	ASTM C140
Absorption	< 5% avg.	ASTM C140
Flexural Strength	Meets or exceeds standard	ASTM C140/C293
Bond Strength	> 300 PSI	ASTM C482
Warpage Edge	+/- .001% or .002 in.	ASTM C485
Warpage Diagonal	+/- .003% or .010 in.	ASTM C485
Nominal Size	Range of .029 in.	ASTM C499
Thickness	Range of .029 in.	ASTM C499
DCOF	Passes at Factory	ASTM A326.3

Testing based on 12" x 12" x 1/2" tile

STANDARD SIZES

24" sq. 5/8" | 16" sq. 5/8" | 12" x 24" 5/8" | 12" sq. 1/2"

Due to the natural variances in materials, the color characteristics of manufactured terrazzo tile may differ slightly from the color swatches pictured. Your monitor or printer may not be an accurate representation of the actual production color or finish.

Custom Colors Available.

CALL FOR FURTHER DETAILS & PRICING.

P: 800.388.8728 | E: wtile@wausautile.com | WAUSAUTILE.COM

Jun 2023